ALUMINIUM SAFETY BICYCLE LIGHT

GEPIDA - TRAFFIC -


FRONT LIGHT

REMIND

Please remove battery insulation sheet before first use.

Step 1

Step 2




INSERT BATTERIES

Remove the battery case then insert 2-CR2032 batteries according to the polarity markings on the case.




INSTALLATION

- 1. Pull the strap to fix into the bulge first.
- 2. Install the light onto the handlebar and tighten it by strap.



TO SWITCH MODES

Press double click to turn on the light & 1 click to switch modes.



SPECIFICATIONS

Size: $40 \times 28 \times 33 \text{ mm}$

Weight: 31 a

LED: Front light: 1 SMD White LED

Rear light: 1 SMD Red LED

Battery: CR2032 x 2

Bracket: Front light: Ø19-Ø32, with 2 rubber pads

Rear light: Ø19-Ø32, with 1 rubber pad



ALUMINIUM SAFETY BICYCLE LIGHT

GEPIDA - TRAFFIC -

REAR LIGHT

REMIND

Please remove battery insulation sheet before first use.

Step 1

Step 2


INSERT BATTERIES

Remove the battery case then insert 2-CR2032 batteries according to the polarity markings on the case




INSTALLATION

- 1. Pull the strap to fix into the bulge first.
- 2. Install the light onto the seat post or seat stay and tighten it by strap.



TO SWITCH MODES

Press double click to turn on the light & 1 click to switch modes.





- 1.We recommend to remove batteries from the light during period of non-use to avoid the battery leakage.
- 2. For best performance, do not mix new and old batteries.
- 3. Carefully install batteries, insuring proper polarity.
- 4. For your own safety, please do not operate the controls of the product while riding.
- 5. Please keep the product out of children's reach.